

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1 1. (Currently amended) A data network for communicating data between a
2 sender unit and a receiver unit, comprising:
3 a core network including relay elements intercoupled by data links;
4 a gateway element coupled to the core network and to the sender unit, the receiver
5 unit being coupled to the core network, the gateway element having at least one information
6 table identifying at least one route from the gateway element through the core network to the
7 receiver unit, including data links which constitute the at least one route, allocations of
8 predetermined communication resources of the data links, and status information indicative of an
9 amount of currently used communication resources of the data links and an amount of currently
10 available communication resources of the data links of the one or more data links.

1 2. (Currently amended) A method of management of data communication
2 through a core network between a sender unit and a receiver unit that includes the steps of:
3 defining at least one communicative route through the core network between the
4 sender unit and the receiver unit that includes a plurality of network links that each have a
5 predetermined communication resource;
6 coupling the sender unit and the receiver unit to the core network with [[a]]
7 sending and receiving gateway elements, respectively;
8 allocating to the sending gateway element a first portion of the predetermined
9 communication resources of at least certain of the network links forming a communicative route
10 between the sending and receiving gateway elements, and maintaining at the sending gateway
11 element information indicative of the allocated predetermined communication resources and

COPY

status information indicative of a currently used amount of the allocated communication
resources and a currently available amount of the allocated communication resources;
receiving at the sending gateway element a request from the sender unit for a data
transfer across the communicative route, the request including a specification of requested
communication resource[[]], the sending gateway element checking the status information to
grant the request if the currently available amount of the allocated communication resources
communicating capacity of the communicative route is equal or greater than the requested
communication resource available.

3. (Original) The method of claim 2, including allocating a second portion
of the predetermined communication resource of the certain of the network links.

4. (Original) The method of claim 3, wherein the step of checking the
information includes reconfiguring the predetermined communicative resource of the certain of
the network links re-allocate at least a portion of the communicative resource allocated to the
receiving gateway element to the sending gateway element.

5. (Previously presented) The method of claim 2, wherein the predetermined
communication resource is a communication bandwidth.

6. (Previously presented) The method of claim 2, wherein the predetermined
communication resource includes a communication bandwidth.

7. (Currently amended) A method of admission control of data to a core
network having a number of relay nodes interconnected by data links, the method including the
steps of:
associating a predetermined data communication capacity with each of the data
communicating links;
communicatively coupling sending and receiving gateway elements to the core
network;

COPY

connecting first and second data transfer elements to the sending and receiving gateway elements, respecting, for data communication by a route through the core network containing certain of the data links;
assigning first and second portions of the data communication capacity of at least the certain of the data links to the sending and receiving gateway elements, respectively;
providing the sending gateway element with information indicative of the first portion[;], the sending gateway element responding to a request for data communication of a requested capacity from the first data transfer element by checking the information, determining status information indicative of currently used data communication capacity of the certain links and currently available data communication capacity of the certain links, and granting the request if the currently available data communication capacity of the certain data links is at least equal to or greater than the requested capacity.

8. (Original) The method of claim 7, wherein the sending step includes re-assigning at least a part of the second portion to the first portion of the data communication capacity of at least one of the certain data links.

9. (Original) The method of claim 8, including the step of providing the receiving gateway element with information indicative of the second portion.

10. (Original) The method of claim 9, wherein the step of re-assigning includes decreasing the information indicative of the second portion by the part of the second portion re-assigned to the first portion.

11. (Original) The method of claim 10, wherein the step of re-assigning includes increasing the information indicative of the first portion by the part of the second portion re-assigned to the first portion.

COPY

12. (Currently amended) A system for providing a QoS communication route from a first communicating entity to a second communicating entity through a core network that includes a plurality of network links, the system including;

a data store comprising an information table of information indicative of a predetermined communication resource associated with each network link;

a sending gateway element and a receiving gateway element respectively coupling the first and second communicating entities to the core network;

assigning wherein the sending gateway element is configured to be assigned a first portion of the predetermined communication resources of at least certain of the network links forming a communicative route between the sending and receiving gateway elements, and to maintaining at the sending gateway element information indicative of the allocated predetermined communication resources and status information indicative of a currently used amount of the allocated communication resources and a currently available amount of the allocated communication resources; and

receiving at wherein the sending gateway element is configured to receive a request from the sender unit for a data transfer across the communicative route, the request including a specification of requested communication resource;

the sending gateway element checking the status information to grant the request if the currently available amount of the allocated communication resources ~~communicating~~ capacity of the communicative route is equal or greater than the requested communication resource available.

13. (New) The data network of claim 1, further comprising:

a trunk management system, wherein the gateway element periodically sends the status information to the trunk management system.

14. (New) The data network of claim 13, wherein the trunk management system allocates bandwidth of the predetermined communication resources of the data links.

COPY

1 15. (New) The method of claim 7, wherein the sending gateway element
2 periodically sends the status information to the trunk management system.

1 16. (New) The method of claim 15, wherein the trunk management system
2 allocates bandwidth of the certain links of the route based on the status information indicative of
3 currently used data communication capacity of the certain links and currently available data
4 communication capacity of the certain links.

COPY